# **Pulsar<sup>®</sup> Precision 30** High-Tech Commercial Pool Disinfection with Powerful Performance

The **Pulsar**<sup>®</sup> Precision 30 feeder is a high capacity erosion (HCE) feeder that is compact and lightweight with a modular design.

The feeder uses **Pulsar**<sup>®</sup> Plus Briquettes that produces a fresh concentrated liquid chlorine solution for clean and sanitized water. This innovative feeder system is easy to maintain and service with a flexible design that allows for easy integration for small to medium size commercial pools.

Switch to the **Pulsar**<sup>®</sup> Precision 30 Feeder System, delivering clear and sparkling water time and time again!



## **Powerful Feeder Performance**

- No booster pump required for feeder operation
- Provides consistent chlorine delivery
  - Feeder designed to minimize maintenance requirements
  - Injection molded components hold up to the strongest elements
- Feeder design allows for easy access to internal components
- Features high capacity erosion technology with the benefits of a venturi

### **Briquette Efficiencies**

- Won't overstabilize pool
- More concentrated than liquid bleach
- Dry, easy to handle formulation
- Will not cause reduction of ORP
- Highly concentrated to reduce shipping and handling costs
- Longer shelf life when compared to liquid bleach

# **Pulsar<sup>®</sup> Precision 30**

#### Secure lid locking feature

puls

Briquette grid Removable for easy maintenance

High capacity erosion nozzle

Emergency shut-off valve to prevent spills

Durable discharge valve

Recommended Pool Size (For guidance only)			
Outdoor Non-Stabilized	Up to 50,000 gal.		
Outdoor Stabilized	Up to 100,000 gal.		
Indoor	Up to 150,000 gal.		
Spas	Up to 10,000 gal.		

Feeder Specifications					
Width	15.5"	393.7 mm			
Depth	19.5"	495.3 mm			
Height	34.0"	863.6 mm			
Water Inlet Size	1/2" MNPT	12 mm MNPT			
Solution Outlet Size	1/2" MNPT	12 mm MNPT			
Operating Weight	52 lbs	23.6 kg			
Shipping Weight	20 lbs	9.1 kg			
Dry Chemical Capacity	30 lbs	13.6 kg			
Electrical		None			
Operating Temperature	40°- 120° F	4.4°-49°C			

<b>Chemical Specification</b>	s		
Active Ingredient			Calcium Hypochlorite
Available Chlorine			68%
Scale Inhibitor			0.4-1.0%
Weight			7-10g
Dimensions	1 ¼″ x	34″ x ½″	33mm x 19mm x 13mm
Chemical Form			Pillow shaped briquette
Color			White
Container	5	50lb pail	22.6kg pail

T



## www.pulsarsystems.net 1.800.4.PULSAR

Pulsar<sup>a</sup> and Pulsar<sup>a</sup> logos are trademarks of Innovative Water Care, LLC or its affiliates. ©2022 Innovative Water Care, LLC